

# **no.1** Gutter Guard

## Installation Guide Tile & Metal Roof

**SAFETY CAUTION:** Accidents can because while working at heights on ladders, trestles and roofs. We urge you to always take care making sure your ladder/platform is firmly secured and to use a harness if working from the roof.

1. Roll out mesh along the entire straight length of the roof & gutter and cut to length. TIP: Secure one end so that the mesh does not roll back or fall off the roof.



2. Attach front edge of mesh to gutter using Trims.

Using the 1000mm long trims ensures that your screws are fixed at the recommended 250mm spacing. Installation can be easier if you first fasten the middle screw on the trim and then come back to the first screw. Remember to keep the mesh securely under the trim.

3. Making cuts in the back of the mesh. Since the mesh does not stretch, it's important to allow 'relief' cuts. Without these cuts, your mesh could tear when you apply pressure on the top tile. The frequency of cuts and where you cut will depend on the type of tile. Tiles with high ribs could require additional or longer cuts.



4. Tuck the mesh under the tile. **(Not apply to metal roof, for metal roof simply screw on with prepared drilled hex head screws )**

5. Finish off hips and ends. This involves cutting around the hips and cutting below the 2nd last row of tiles that are cemented to the hip (pic 14). Then bond mesh to tiles and hip using silicon.



Contact Info [info@no1gutterguard.com.au](mailto:info@no1gutterguard.com.au)

Shop Online Store [www.no1gutterguard.com.au](http://www.no1gutterguard.com.au)